

PX45 AND PX65 SERIES PRINTERS



High-Performance Industrial Printers

The PX45 and PX65 Series industrial printers are built to meet the needs of round-the-clock, mission-critical applications. These rugged printers deliver advanced connectivity and network protocols, ensuring peace of mind today and a reliable, scalable solution for the long haul.



The rugged, all-metal PX45 and PX65 printers deliver outstanding performance – up to 12 inches per second from first label to last – and incorporate features that reduce downtime and minimize maintenance costs. Both versions are available with 203 or 300 dpi resolution, and the PX45 also offers 406 dpi, for precision labeling without any loss of speed. This is ideal for compliance labeling applications with variable data requiring immediate results.

The PX45 and PX65 Series industrial printers are flexible, compact, and programmable, enabling customers to optimize their printing operations, streamline deployment, and achieve quick return on investment.

The PX45 and PX65 printers' smart design features support increased productivity in demanding environments. As Smart Printers, they can host stand-alone applications, developed through the Fingerprint and C# programming languages, helping reduce errors and streamline operational processes.

The printers' device management and diagnostic capabilities – provided in web-based PrintSet 5 Configuration Management tool, configuration tool PrintSet MC for mobile devices and cloud-based Operational Intelligence– reduce downtime and simplify deployment. Replacing printheads is fast and easy, thanks to the magnetic QuickMount™ printhead design. The PX45 and PX65 printers are co-engineered and tested with Honeywell labels and other media products, optimizing performance when used with genuine Honeywell media.

FEATURES AND BENEFITS



The PX45 and PX65 printers' compact, modular design facilitates integration into automated labeling applications.



Smart Printers can eliminate the PC and control other devices directly (such as scanners, scales, and applicators), improving efficiency and decreasing infrastructure costs and complexity.



With user-selectable, all-in-one printer command languages (DP/FP, IPL, ZSim, DPL), the PX45 and PX65 printers fit with drop-in simplicity in mixed printer environments, supporting fast deployment.



Every printer ships with 10/100 Mbps Ethernet connectivity and high speed USB ports, ensuring long-term, enterprise scalability. Multiple interface options are available.

PX45 and PX65 Series Printers Technical Specifications



PHYSICAL CHARACTERISTICS

PX45:

L x H x W:
482 mm x 238 mm x 275 mm
(19.0 in x 9.4 in x 10.8 in)

Weight:
12.61 kg (27.87 lbs)

PX65:

L x H x W:
482 mm x 238 mm x 335mm
(19.0 in x 9.4 in x 13.2 in)

Weight:
14.1 kg (31.12 lbs)

PX45/65 PRINT SPECIFICATIONS

Max. Width:

PX45: 112 (DT)/110 (TT) mm (4.4/4.3 in)
PX65: 167.4 mm (6.59 in)

WIRELESS CONNECTIVITY

WLAN:

IEEE 802.11 a/b/g/n/ac
Wi-Fi Certified
WEP, WPA, WPA2, 802.11x (EAPTTLS,
LEAP, PEAP, FAST)

RFID Standards & Frequencies

Supports 18000-6C / EPC Generation 2
865-928 MHz radio configured to comply
with local UHF RFID regulations including
FCC and ETSI. Contact local representative for
availability in particular region.

PRINT SPEED

PX45:

At 203/300 dpi: 100–300 mm/s (4–12 ips)
At 406 dpi: 100–250 mm/s (4–10 ips)

PX65:

At 203/300 dpi: 100–225 mm/s (4–9 ips)

Print Resolution

PX45:

At 203 dpi: 8 dots/mm
At 300 dpi: 11.8 dots/mm
At 406 dpi: 16 dots/mm

PX65:

At 203 dpi: 8 dots/mm
At 300 dpi: 11.8 dots/mm

BARCODES/FONTS/GRAPHICS

Barcode Symbolologies: All major 1D and 2D
symbolologies are supported

Standards Supported: UPC/EAN Shipping
Container, UCC/EAN 128, Serial Shipping
Container, MH10.8 Shipping Label, AIAG
(shipping parts label), OGMARS, POSTNET,
HIBCC, ISBT 128, GM1724, UPS Shipping
Label, Global Transport Label

For more information

sps.honeywell.com

Fonts

Monotype font engine
Non-Latin fonts available through WTLE

Graphics

Supports PCX, PNG, GIF and BMP file formats.
Other formats supported with Label
Generation Tools.

Memory

Standard: 512 MB Flash memory, 256 MB
SDRAM, Multi-GB USB memory device
(FAT16/FAT22)

User Partitioning: 256 MB

USER INTERFACE LANGUAGES

On Full Touch LCD and Web Interface:

English, Russian, German, French,
Portuguese, Spanish, Italian, Korean, Thai,
Japanese, Simplified and Traditional Chinese

POWER SUPPLY

On Full Touch LCD and Web Interface:

AC Voltage: 90 to 265V AC, 45 to 65 Hz
Power Consumption: Standby 5W;
Peak 400W

MEDIA SPECIFICATION

Type: Labels and Tags and Lined media

Max./Min.Width:

PX45: 120/25.4 mm (4.72/1 in)
PX65: 170/76 mm (6.70/3 in)

Thickness: 2.4 to 10.0 mil

Configuration: Roll-fed or fan-fold

Media Sensing: Gap, Notch, Black mark,
Continuous, Media low, Media end

Other sensing: Label Taken sensing, Ribbon
Low/End sensing, Head lift sensing

Label Roll Max.Diameter: 213 mm
(8.38 in)

Label Roll Core ID: 38–76 mm (1.5–3 in)

Type: Wax, mid-range, resin

Ribbon Specification:

Type: Wax, mid-range and resin
Max.Ribbon Diameter: 80mm (3.15in)

Genuine Honeywell Media:

[https://sps.honeywell.com/us/en/products/
productivity/printer-supplies](https://sps.honeywell.com/us/en/products/productivity/printer-supplies)

INTERFACES

Standard:

Ethernet 10/100 Mbps
USB 2.0 Host High Speed
USB 2.0 Device High Speed
RS-232, up to 115.2 KB/s

Optional:

Parallel: IEEE 1284
Industrial Interface: 8 digital in/out, 4
analog relays, 1 RS-232/422/485 port
Dual Serial Ports: RS-232, RS-422,
RS-485, and 20 mA Current Loop
Applicator Interface

Supported Network Protocols:

TCP/IP suite (TCP, UDP, ICMP, IGMP), LPR/
LPD, Telnet/SSH, FTP/SFTP, BOOTP,
DHCP, HTTP/HTTPS, SNMPv1/2c/3,
SNMP-MIBII supported – over UDP/IP
(private enterprise MIB included), SMTP
Supports IPv4 and IPv6

SOFTWARE

Printer Command Languages:

Fingerprint (FP)
Direct Protocol (DP)
Intermec Printer Language (IPL)
ZSim2 (ZPL-II)
DPL
XML-enabled for SAP All and Oracle WMS
PDF
C#

Applications/Drivers:

InterDriver Windows printer driver, CUPS driver
for Linux, Honeywell Device Types for SAP,
Honeywell label design and print package

Smart Printing Languages:

C# for Printers: Honeywell Smart Printing
Developer Resource Kit; write apps with .NET-
compatible development environments.

Configuration and Device

Management Support (optional):

OpIntel - PrintSet 5 for printer configuration;
sophisticated web interface for configuration,
upgrades and 1:1 management.

OPERATING ENVIRONMENT

Ambient Operating Temperature:

+5°C to +40°C (+41°F to +104°F)

Storage Temperature:

-20°C to +70°C (-4°F to +152°F)

Operating Humidity:

10 to 90% non-condensing

Storage Humidity:

10 to 90% non-condensing

Regulatory approvals

RoHS Compliant, CE (EN55032 Class B*),
FCC Class B*, Energy Star 3.0 Qualified
For more countries compliant, please
contact your local sales office.

OPTIONS AND ACCESSORIES

**Consult the PX45 and PX65 Accessory Guide
for full details.**

RFID, parallel interface board, additional serial
interface board*, industrial interface board*,
applicator interface board**, media supply
hub, cutter

*Not applicable when using IPL firmware.

** Supported for Direct Protocol and
Fingerprint printer languages.